

General Description

The LTA809x family (LTA8091, LTA8092, and LTA8094) is a new generation of high voltage (48 V), low noise, precision operational amplifiers. These devices offer outstanding dc precision and ac performance, including low offset, low offset drift, 22-MHz bandwidth, and 4 nV/√Hz input voltage noise density at 10 kHz. Unique features such as differential input-voltage range to the negative supply rail, high output current (± 45 mA), high capacitive load drive of up to 1 nF, and high slew rate (20 V/μs) make the LTA809x high-performance operational amplifiers for high-voltage industrial and medical applications.

The robust design of the LTA809x family provides ease-of-use to the circuit designer: integrated RF/EMI rejection filter, no phase reversal in overdrive conditions, and high electro-static discharge (ESD) protection. The LTA809x are optimized for operation at voltages from +4.5 V (± 2.25 V) to +48 V (± 24 V) over the extended temperature range of -40 °C to $+125$ °C.

The LTA8091 (single) is available in both SOT23-5L and SOIC-8L packages. The LTA8092 (dual) is offered in SOIC-8L and MSOP-8L packages. The quad-channel LTA8094 is offered in both SOIC-14L and TSSOP-14L packages.


Features and Benefits

- Wide Supply: ± 2.25 V to ± 24 V, 4.5 V to 48 V
- Wide Bandwidth: 22 MHz GBW
- High Slew Rate: 20 V/μs
- Low Noise: 4 nV/√Hz at 10 kHz
- Low Offset Voltage: ± 350 μV Maximum
- Low Offset Voltage Drift: ± 1.5 μV/°C
- High Common-Mode Rejection: 116 dB
- Low Bias Current: ± 10 pA
- EMI/RFI Filtered Inputs

Applications

- High-Side and Low-Side Current Sensing
- Audio Preamplifier
- High Precision Comparator
- Multiplexed Data-Acquisition Systems
- High-Resolution ADC Driver Amplifiers
- SAR ADC Reference Buffers
- Test and Measurement Equipment
- Programmable Logic Controllers

Pin Configuration (Top View)



Pin Description

Symbol	Description
-IN	Inverting input of the amplifier. The voltage range is from V_{S-} to $V_{S+} - 1.5$ V.
+IN	Non-inverting input of the amplifier. This pin has the same voltage range as -IN.
+V _S	Positive power supply. The voltage is from 4.5 V to 48 V. Split supplies are possible as long as the voltage between V_{S+} and V_{S-} is from 4.5 V to 48 V.
-V _S	Negative power supply. It is normally tied to ground. It can also be tied to a voltage other than ground as long as the voltage between V_{S+} and V_{S-} is from 4.5 V to 48 V.
OUT	Amplifier output.
NC	No connection

Ordering Information ⁽¹⁾

Type Number	Package Name	Package Quantity	Eco Class ⁽²⁾	Marking Code ⁽³⁾
LTA8091XT5/R6	SOT23-5L	Tape and Reel, 3 000	Green (RoHS & no Sb/Br)	H91
LTA8091XS8/R8	SOIC-8L	Tape and Reel, 4 000	Green (RoHS & no Sb/Br)	HV-91
LTA8092XS8/R8	SOIC-8L	Tape and Reel, 4 000	Green (RoHS & no Sb/Br)	HV-92
LTA8092XV8/R6	MSOP-8L	Tape and Reel, 3 000	Green (RoHS & no Sb/Br)	HV92
LTA8092XF8/R6	DFN3x3-8L	Tape and Reel, 3 000	Green (RoHS & no Sb/Br)	HV92
LTA8094XS14/R5	SOIC-14L	Tape and Reel, 2 500	Green (RoHS & no Sb/Br)	HV-94
LTA8094XT14/R6	TSSOP-14L	Tape and Reel, 3 000	Green (RoHS & no Sb/Br)	HV-94

(1) Please contact to your Linearin representative for the latest availability information and product content details.

(2) Eco Class - The planned eco-friendly classification: Pb-Free (RoHS) or Green (RoHS & Halogen Free).

(3) There may be multiple device markings, a varied marking character of "x", or additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

Limiting Value – In accordance with the Absolute Maximum Rating System (IEC 60134).

Parameter	Absolute Maximum Rating
Supply Voltage, V_{S+} to V_{S-}	60 V
Signal Input Terminals: Voltage, Current	$-V_S - 0.3$ V to $+V_S + 0.3$ V, ± 10 mA
Output Short-Circuit	Continuous
Storage Temperature Range, T_{stg}	-65 °C to $+150$ °C
Junction Temperature, T_J	150 °C
Lead Temperature Range (Soldering 10 sec)	260 °C

ESD Rating

Parameter	Item	Value	Unit
Electrostatic Discharge Voltage	Human body model (HBM), per MIL-STD-883J / Method 3015.9 ⁽¹⁾	2 000	V
	Charged device model (CDM), per ESDA/JEDEC JS-002-2014 ⁽²⁾	2 000	

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 500-V HBM is possible if necessary precautions are taken.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 250-V CDM is possible if necessary precautions are taken.

P-3

LTA8091, LTA8092, LTA8094

48 V, 22 MHz, Low Noise, Precision Operational Amplifiers

Electrical Characteristics

 $V_S = 4.5 \text{ V to } 48 \text{ V}$, $T_A = +25 \text{ }^\circ\text{C}$, $V_{CM} = V_{OUT} = V_S/2$, and $R_L = 10 \text{ k}\Omega$ connected to $V_S/2$, unless otherwise noted.

 Boldface limits apply over the specified temperature range, $T_A = -40 \text{ }^\circ\text{C to } +125 \text{ }^\circ\text{C}$.

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
OFFSET VOLTAGE						
Input offset voltage	V_{OS}	$V_S = 5 \text{ V}$		± 25	± 100	μV
					± 350	
Offset voltage drift	$V_{OS \text{ TC}}$	$T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		± 1.5		$\mu\text{V}/^\circ\text{C}$
Power supply rejection ratio	PSRR	$V_S = 4.5 \text{ to } 48 \text{ V}$, $V_{CM} = 0.1 \text{ V}$		3.5		$\mu\text{V/V}$
		$T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		10		
INPUT BIAS CURRENT						
Input bias current	I_B			10		
		$T_A = -40 \text{ to } +85 \text{ }^\circ\text{C}$		150		pA
		$T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		600		
Input offset current	I_{OS}			5		pA
NOISE						
Input voltage noise	V_n	$f = 0.1 \text{ to } 10 \text{ Hz}$		3.6		μV_{P-P}
Input voltage noise density	e_n	$f = 1 \text{ kHz}$		8		$\text{nV}/\sqrt{\text{Hz}}$
		$f = 10 \text{ kHz}$		4		
Input current noise density	i_n	$f = 1 \text{ kHz}$		5		$\text{fA}/\sqrt{\text{Hz}}$
INPUT VOLTAGE						
Common-mode voltage range	V_{CM}		$-V_S$		$+V_S - 1.5$	V
Common-mode rejection ratio	CMRR	$V_S = 40 \text{ V}$, $V_{CM} = 0 \text{ to } 38 \text{ V}$		116		dB
		$V_{CM} = 0.1 \text{ to } 38 \text{ V}$, $T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		103		
		$V_S = 5 \text{ V}$, $V_{CM} = 0 \text{ to } 3.5 \text{ V}$		96		
		$V_{CM} = 0.1 \text{ to } 3 \text{ V}$, $T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		84		
INPUT IMPEDANCE						
Input capacitance	C_{IN}	Differential		2		pF
		Common mode		3.5		
OPEN-LOOP GAIN						
Open-loop voltage gain	A_{VOL}	$V_S = 40 \text{ V}$, $V_O = 0.1 \text{ to } 39.9 \text{ V}$		130		dB
		$T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		120		
		$V_S = 5 \text{ V}$, $V_O = 0.1 \text{ to } 4.9 \text{ V}$		122		
		$T_A = -40 \text{ to } +125 \text{ }^\circ\text{C}$		112		
FREQUENCY RESPONSE						
Gain bandwidth product	GBW			22		MHz
Slew rate	SR	$V_S = 40 \text{ V}$, $G = +1$, 10 V step		20		$\text{V}/\mu\text{s}$
Total harmonic distortion + noise	THD+N	$G = +1$, $f = 1 \text{ kHz}$, $V_O = 3 \text{ V}_{RMS}$		0.0001		%
Settling time	t_S	To 0.1%, $V_S = 40 \text{ V}$, $G = +1$, 5 V step		0.9		μs
		To 0.01%, $V_S = 40 \text{ V}$, $G = +1$, 5 V step		2		
Overload recovery time	t_{OR}	$V_{IN} \times \text{Gain} > V_S$		0.3		μs

CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.

Linearin and designs are registered trademarks of Linearin Technology Corporation.

© Copyright Linearin Technology Corporation. All Rights Reserved.

All other trademarks mentioned are the property of their respective owners.




Electrical Characteristics (continued)

$V_S = 4\text{ V to }48\text{ V}$, $T_A = +25\text{ }^\circ\text{C}$, $V_{CM} = V_{OUT} = V_S/2$, and $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, unless otherwise noted.
Boldface limits apply over the specified temperature range, $T_A = -40\text{ }^\circ\text{C to }+125\text{ }^\circ\text{C}$.


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
OUTPUT						
High output voltage swing	V _{OH}	V _S = ±20 V, R _L = 10 kΩ		+V _S -95		mV
		V _S = ±20 V, R _L = 2 kΩ		+V _S -260		
Low output voltage swing	V _{OL}	V _S = ±20 V, R _L = 10 kΩ		-V _S +55		mV
		V _S = ±20 V, R _L = 2 kΩ		-V _S +240		
Short-circuit current	I _{SC}			±45		mA
POWER SUPPLY						
Operating supply voltage	V _S	T _A = -40 to +125 °C	4.5		48	V
Quiescent current (per amplifier)	I _Q	V _S = 5 V		4.2		mA
		V _S = 40 V		7.1		
THERMAL CHARACTERISTICS						
Operating temperature range	T _A		-40		+125	°C
Package Thermal Resistance	θ _{JA}	SOT23-5L		190		°C/W
		MSOP-8L		201		
		SOIC-8L		125		
		TSSOP-14L		112		
		SOIC-14L		115		

Typical Performance Characteristics


At $T_A = +25\text{ }^{\circ}\text{C}$, $V_{CM} = V_S/2$, and $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, unless otherwise noted.




Offset Voltage Production Distribution




Input Voltage Noise Spectral Density as a function of Frequency




CMRR as a function of Frequency



PSRR as a function of Frequency



Open-loop Gain and Phase as a function of Frequency




Close-loop Gain as a function of Frequency

CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.
Linearin and designs are registered trademarks of Linearin Technology Corporation.
© Copyright Linearin Technology Corporation. All Rights Reserved.
All other trademarks mentioned are the property of their respective owners.




Typical Performance Characteristics (Continued)


At $T_A = +25^\circ\text{C}$, $V_{CM} = V_S/2$, and $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, unless otherwise noted.




Quiescent Current as a function of Supply Voltage




Quiescent Current as a function of Temperature




Bias Current as a function of Common-Mode Voltage



Output Voltage Swing as a function of Output Current (Sinking, $V_S = 40\text{ V}$)



Output Voltage Swing as a function of Output Current (Sourcing, $V_S = 40\text{ V}$)




Large-Signal Step Response(Rising)

CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.
Linearin and designs are registered trademarks of Linearin Technology Corporation.
© Copyright Linearin Technology Corporation. All Rights Reserved.
All other trademarks mentioned are the property of their respective owners.




Typical Performance Characteristics (Continued)

At $T_A = +25\text{ }^{\circ}\text{C}$, $V_{CM} = V_S/2$, and $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, unless otherwise noted.




Large-Signal Step Response(Failing)




Small-Signal Step Response

Tape and Reel Information

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE




* All dimensions are nominal


Device	Package Type	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin 1 Quadrant
LTA8091XT5/R6	SOT23	5	3 000	178	9.0	3.3	3.2	1.5	4.0	8.0	Q3

Package Outlines

DIMENSIONS, SOT23-5L




RECOMMENDED SOLDERING FOOTPRINT, SOT23-5L




Package Outlines (continued)

DIMENSIONS, SOIC-8L




RECOMMENDED SOLDERING FOOTPRINT, SOIC-8L




Package Outlines (continued)

DIMENSIONS, MSOP-8L




RECOMMENDED SOLDERING FOOTPRINT, MSOP-8L



CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.
Linearin and designs are registered trademarks of Linearin Technology Corporation.
© Copyright Linearin Technology Corporation. All Rights Reserved.
All other trademarks mentioned are the property of their respective owners.


Package Outlines (continued)

DIMENSIONS, DFN3x3-8L




Package Outlines (continued)

DIMENSIONS, SOIC-14L




RECOMMENDED SOLDERING FOOTPRINT, SOIC-14L




Package Outlines (continued)

DIMENSIONS, TSSOP-14L



RECOMMENDED SOLDERING FOOTPRINT, SOIC-14L



Important Notice

Linearin is a global fabless semiconductor company specializing in advanced high-performance high-quality analog/mixed-signal IC products and sensor solutions. The company is devoted to the innovation of high performance, analog-intensive sensor front-end products and modular sensor solutions, applied in multi-market of medical & wearable devices, smart home, sensing of IoT, intelligent industrial & smart factory (industrie 4.0), and automotives. Linearin's product families include widely-used standard catalog products, solution-based application specific standard products (ASSPs) and sensor modules that help customers achieve faster time-to-market products. Go to <http://www.linearin.com> for a complete list of Linearin product families.

For additional product information, or full datasheet, please contact with the Linearin's Sales Department or Representatives.